

ProCash 1500xe

Monofunction cash dispenser
for lobby installations



Compact design
and minimum
footprint

Bundle output
of up to 60 notes

Optimized cash
management

Designed for use
by people with
disabilities

Flexible deploy-
ment, inclusive
off-premise

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 1500xe

Monofunction cash dispenser

The ProCash 1500xe is the entry-level system in Wincor Nixdorf's ProCash product family. With its compact size, it is the ideal system for locations at which space is limited and the focus is on cash handling.

Featuring up to four cassettes, the ProCash 1500xe also guarantees maximum availability in installations outside bank foyers, for example at service stations or supermarkets.

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)

CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06
- Various card retract compartments

CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm

- Note reject/bundle retract, storage in separate compartments
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Cash slot camera
- Portrait camera
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Business Hours
- UL 291 Level 1
- CEN L (for rearload only)

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

BARCODE READER

- Able to read and process various barcode formats

MARKETING FEATURES

- Illuminated logo panel
- Illuminated topper
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5° C to + 40° C

RELATIVE HUMIDITY

- 5% to 85%

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS

