

ProCash 2100xe

Multifunction ATM
for lobby installations



Coin deposits
in sidecar >

Bundle output
up to 60 notes >

Optimized cash
management >

Designed for use
by people with
disabilities >

< Intelligent
cash and check
deposits

< Comprehensive
security
solutions

< Open hardware
and software
architectures

< Project-specific
solutions



DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5 PCI) or alpha kombi or multi keyboard
- PIN shield (VISA-compliant)
- Alphanumeric/EPP kombi keyboard

CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06/MM
- Various card retract compartments

CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Cash slot camera
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV
- CEN L

PRINTERS

- Receipt and journal printer (dot matrix or thermal)
- Statement/information printer (dot matrix or thermal)

PASSBOOK PROCESSING

- Passbooks with a horizontal fold
- ZeKoSa reading unit, page-turning function and last line recognition
- Optional retract and/or deposit compartment for passbooks and loose sheets

COIN PROCESSING

- 6 or 8 coin hoppers

BARCODE READER

- Able to read and process various barcode formats

CASH DEPOSITS

ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 or 300 envelopes depending on the deposit compartment, optional security compartment

CASH/CHECK DEPOSIT MODULE

Banknote processing

- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm or 385 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

Check processing

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm or 385 mm
- Cassettes with lock
- Scanner module for single or bundled checks
 - MICR (E13B or CMC7)
 - OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5°C to + 40°C

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS

