

# ProCash 2250xe

Multifunction ATM  
for outdoors, drive-up model



Space-saving  
drive-up  
installation

Bundle output  
up to 60 notes

Optimized cash  
management

Designed for use  
by people with  
disabilities

Intelligent  
cash and check  
deposits

Comprehensive  
security  
solutions

Open hardware  
and software  
architectures

Project-specific  
solutions



## Technical Data

## ProCash 2250xe

### DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

### KEYBOARD

- Encrypting PIN pad (EPP V5 PCI)
- PIN shield (VISA-compliant)

### CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06/MM
- Various card retract compartments

### CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Note reject/bundle retract, storage in separate compartments

- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

### SECURITY

- Intruder alarm
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

### SAFES

- UL 291 Level 1

### PRINTERS

- Receipt and journal printer (dot matrix or thermal)
- Statement/information printer (dot matrix or thermal)

### ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 or 300 envelopes depending on the deposit compartment, optional security compartment

### CASH/CHECK DEPOSIT MODULE

#### Banknote processing

- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

#### Check deposits

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Scanner module for single or bundled checks
  - MICR (E13B or CMC7)
  - OCR image processing

### MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

### AUDIO

- Loudspeakers
- Headset jack

### OPERATING SYSTEM

- Windows XP

### POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

### TEMPERATURE RANGE

- + 5° C to + 40° C
- Customer fascia - 40° C to + 50° C (with heating)

### RELATIVE HUMIDITY

- 5 % to 85 %

### INSTALLATION

- Rearload
- Outdoors
- Drive-up

### APPROVALS

